

# UPS INTERACTIVAS

750/1000/2000

GCO - FT - 037	
RVO	MAY-14

Model	UPS 750	UPS 1000	UPS 2000
CAPACITY	750 VA / 360 W	1000 VA / 600 W	2000 VA / 1200 W
<b>INPUT</b>			
Voltage	110/120 VAC		
Voltage Range	90 - 145 VAC		
Frequency Range	60/50 Hz (auto sensing)		
<b>OUTPUT</b>			
AC Voltage Regulation (Batt. Mode)	+/- 10%		
Frequency Range (Batt. Mode)	60 Hz or 50 Hz +/- 1Hz		
Transfer Time	Typical 2-6 ms, 10ms max.		
Waveform (Batt. Mode)	Simulated Sine Wave		
<b>BATTERY</b>			
Battery Type & Number	12 V/7.5 Ah x 1	12 V/7 Ah x 2	12 V/9 Ah x 2
Typical Recharge Time	4-6 hours recover to 90% capacity		
<b>PROTECTION</b>			
Full Protection	Overload, discharge, and overcharge protection		
<b>INDICATORS</b>			
LCD Display	N/A		
LED Display	AC Mode	Green lighting	Green lighting
	Battery Mode	Green flashing	Yellow flashing
	Fault	N/A	Red lighting
<b>ALARM</b>			
Battery Mode	Sounding every 10 seconds		
Low Battery	Sounding every second		
Overload	Sounding every 0.5 second		
Battery Replacement Alarm	Sounding every 2 seconds		
Fault	Continuously sounding		
<b>PHYSICAL</b>			
Dimension, D x W x H (mm)	330 x 100 x 140	365 x 139 x 195	
Net Weight (kgs)	6	8.6	10.2
<b>ENVIRONMENT</b>			
Humidity	0-90 % RH @ 0- 40°C (non-condensing)		
Noise Level	Less than 40dB		
<b>MANAGEMENT</b>			
Optional USB/RS-232 Port	Supports Windows <sup>®</sup> 98/2000/2003/XP/Vista/2008, Windows <sup>®</sup> 7, Linux and MAC		

\* Product specifications are subject to change without further notice



SPECTRONIC LTDA  
 CARRERA 14 No. 98-31 PBX. 623 00 55 BOGOTA COLOMBIA  
 www.spectronic.com.co / E-Mail: servicio@spectronic.com.co