UPS INTERACTIVAS

750/1000/2000

GCO - FT - 037	
RV 0	MAY-14

Model		UPS 750	UPS 1000	UPS 2000
CAPACITY		750 VA / 360 W	1000 VA / 600 W	2000 VA / 1200 W
INPUT				
Voltage		110/120 VAC		
Voltage Range		90 - 145 VAC		
Frequency Range		60/50 Hz (auto sensing)		
OUTPUT				
AC Voltage Regulation (Batt. Mode)		+/- 10%		
Frequency Range (Batt. Mode)		60 Hz or 50 Hz +/- 1Hz		
Transfer Time		Typical 2-6 ms, 10ms max.		
Waveform (Batt. Mode)		Simulated Sine Wave		
BATTERY				
Battery Type & Number		12 V/7.5 Ah x 1	12 V/7 Ah x 2	12 V/9 Ah x 2
Typical Recharge Time		4-6 hours recover to 90% capacity		
PROTECTION				
Full Protection		Overload, discharge, and overcharge protection		
INDICATORS				
LCD Display		N/A		
LED Display	AC Mode	Green lighting		Green lighting
	Battery Mode	Green fashing		Yellow fashing
	Fault	N/A		Red lighting
ALARM				
Battery Mode		Sounding every 10 seconds		
Low Battery		Sounding every second		
Overload		Sounding every 0.5 second		
Battery Replacement Alarm		Sounding every 2 seconds		
Fault		Continuously sounding		
PHYSICAL				
Dimension, D x W x H (mm)		330 x 100 x 140	365 x 139 x 195	
Net Weight (kgs)		6	8.6	10.2
ENVIRONMENT				
Humidity		0-90 % RH @ 0- 40°C (non-condensing)		
Noise Level		Less than 40dB		
MANAGEMENT				
Optional USB/RS-232 Port		Supports Windows² 98/2000/2003/XP/Vista/2008, Windows² 7, Linux and MAC		

* Product specifcations are subject to change without further notice

SPECTRONIC

SPECTRONIC SAS
CARRERA 14 No. 98-31 PBX. 623 00 55 BOGOTA COLOMBIA
www.spectronic.com.co / E-Mail: servicio@spectronic.com.co